2 West Main Street
Victor, NY 14564
585-461-2110
sales@mctram.com

MCT/RAM Providing Engineered Solutions Since 1984

Order Form

Ordering code DMK 351

DMK 351 □□□-□□□□-□-□-□□□-□□□-□-□-□-□□□

Option		Code	
Pressure			
in bar, gauge		2 9 0	
in bar, absolute		2 9 1	
in bar, sealed gauge			consult
in mH_2O, gauge		2 9 2	
in mH_2O, absolute		2 9 3	consult
in mH_2O, sealed gauge			consult
Input [mH_2O]	[bar]		
0.4	0.04	0 4 0 0	
0.6	0.06	0 6 0 0	
1.0	0.10	1 0 0 0	
1.6	0.16	1 6 0 0	
2.5	0.25	2 5 0 0	
4.0	0.40	4 0 0 0	
6.0	0.60	6 0 0 0	
10	1.0	1 0 0 1	
16	1.6	1 6 0 1	
25	2.5	2 5 0 1	
40	4.0	4 0 0 1	
60	6.0	6 0 0 1	
100	10	1 0 0 2	
160	16	1 6 0 2	
200	20	2 0 0 2	
customer		9 9 9 9	consult
Output			
4 … 20 mA / 2-wire		1	
0 … 10 V / 3-wire		3	
Intrinsic safety 4 … 20 mA / 2-wire		E	
customer		9	consult
Accuracy			
standard	0.35 %	3	
option für $P_N \geq 0$	0.25 %	2	
customer		9	consult
Electrical connection			
Male and female plug ISO 4400		1 0 0	
Male plug Binder series 723 (5-pin)		2 0 0	
Cable outlet with PVC cable [1]		T A 0	
Cable outlet with cable		T R 0	
Male plug M12x1 (4-pin) / metal		M 1 0	
compact field housing stainless steel 1.4305		8 5 0	
customer		9 9 9	consult
Mechanical connection			
G1/2" DIN 3852		1 0 0	
G1/2" EN 837		2 0 0	
1/2" NPT		N 0 0	
customer		9 9 9	consult
Seals			
FKM		1	
EPDM		3	
customer		9	consult
Pressure port			
Stainless steel 1.4404 (316L)		1	
customer		9	consult
Diaphragm			
Ceramics Al_2O_3 96%		2	
Ceramics Al_2O_3 99.9 %		C	
customer		9	consult
Special version			
standard		0 0 0	
customer		9 9 9	consult

[1] standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 … 70 °C), optionally cable with ventilation tube

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

Please visit our website: www.mctram.com