

Order Form SRP-94 / SRP-946

ORDERING

SRP-X-1XXX-1-X-XX1

display: _____

94 : 4-digits

946 : 6-digits

type of input: _____

8 : 0-20 mA, 4-20 mA, 0/1-5V, 0/2-10V **C** :
 0-60/75/100/150 mV

number of outputs: _____

0
2
3
4

type of outputs: _____

0 : no output
1 : REL (for 2 and 4 outputs)
2 : OC (for 2 and 4 outputs)
3 : 2 x REL + 1 x AO (0/4-20 mA, active, non-isolated)
4 : 2 x OC + 1 x AO (0/4-20 mA, active, non-isolated)
9 : 2 x REL + 1 x AO (4-20 mA, passive, isolated)
A : 2 x OC + 1 x AO (4-20 mA, passive, isolated)
B : 2 x REL + 1 x AO (0/1-5V, 0/2-10V, active, non-isolated) **C** : 2 x OC
 + 1 x AO (0/1-5V, 0/2-10V, active, non-isolated)

options:

00 : no options
01 : IP 65 frame
03 : green colour LED display
04 : IP 65 frame + green colour LED display
08 : operating temp. -20°C ÷ +50°C
0P : IP 65 frame + operating temp. -20°C ÷ +50°C
0L : green colour LED display + operating temp. -20°C ÷ +50°C **0T** : IP 65
 frame + green colour LED display

+ operating temp. -20°C ÷ +50°C

power supply:

3 : 24V AC/DC
4 : 85V - 260V AC/DC

