Ordering code DM01

2. position: digital display for Precision Digital Pressure Gauge DL01

DM01- ☐☐☐

Digital pressure gauge DM01				
with communication interface	A	2	1	
IS with communication interface	A	2	E	

2. position: transmitter for Precision Digital Pressure Gauge DM01

DM01 ☐☐☐-☐☐☐☐-☐-☐☐-☐☐☐-☐-☐☐☐

Pressure																			
gauge		M	0	K															
absolute	[1]	M	0	L															
Input	**[bar]**																		
0.10	[1]				1	0	0	0											
0.16	[1]				1	6	0	0											
0.25	[1]				2	5	0	0											
0.40					4	0	0	0											
0.60					6	0	0	0											
1.0					1	0	0	1											
1.6					1	6	0	1											
2.5					2	5	0	1											
4.0					4	0	0	1											
6.0					6	0	0	1											
10					1	0	0	2											
16					1	6	0	2											
25					2	5	0	2											
40					4	0	0	2											
60					6	0	0	2											
100					1	0	0	3											
160					1	6	0	3											
250					2	5	0	3											
400					4	0	0	3											
-1 ... 0					X	1	0	2											
customer					9	9	9	9											consult
version																			
non IS									0										
IS									E										
Accuracy																			
standard for $P_N \geq 0.4$ bar	0.05%									B	1								
standard for $P_N < 0.4$ bar	0.125%									B	2								
customer										9	9								consult
Mechanical connection																			
G1/2" DIN 3852												1	0	0					
G1/2" EN 837												2	0	0					
G1/4" DIN 3852												3	0	0					
G1/4" EN 837												4	0	0					
G1/2" DIN 3852 with flush sensor	[2]											F	0	0					consult
G1/2" DIN 3852 open pressure port												H	0	0					
1/2" NPT												N	0	0					
1/4" NPT												N	4	0					
customer												9	9	9					consult
Seals																			
FKM															1				
customer															9				consult
Special version																			
standard																0	0	0	
customer																9	9	9	consult

[1] *absolute pressure possible from 0.4 bar*
[2] *only possible for $P_N \leq 40$ bar*

ordering example:
device DM01:
position 1: DM 01-A21
position 2: M0K-1001-B1-200-1-000
only display: position 1: DM01-A21
only transmitter: position 2: M0K-1001-B1-200-1-000