

LVS-9510 Specifications

Physical Properties

Diameter	9.062 inches (230 mm)
Width	11.125 inches (282 mm)
Height	10.5 inches (266.7 mm)
Viewing Window	5 inches x 7 inches (127 mm x 177.79 mm)
Unpackaged weight (standalone LVS-9510 unit)	6 pounds (2.72 kg)
Shipping weight (includes all items packaged in shipping box, such as power supply, cables, manuals, etc.)	13 pounds (5.89 kg)
Top Cover - Dimensions	5.5 inches x 7.5 inches (139.7 mm x 190.5 mm)
Top Cover - Weight	5.5 oz (162.65 grams)
Video Camera	Monochrome 5.0 megapixel
Light Source	White Light Red (660 nm) filter.
Optional clear window available for purchase.	
Electrical	USB 2.0 port
Power Supply	12 vdc @ 2.5 amps (minimum)
Operating Temperature	10° C (50° F) to 30° C (86° F)
Storage Temperature	0° C (32° F) to 40° C (104° F)
Relative Humidity	20% to 70% (non-condensing)

Calibration:
 One of the following:

EAN/UPC Calibrated Conformance Test Card (LVS® part # CAL002)

GS1-128 Calibrated Conformance Test Card (LVS® part # CAL003)

Minimum PC Requirements:

Windows® XP Professional, Windows® 7, Windows® 10

Intel® Core™ 2 Duo Processor (or equivalent)

2 GB RAM

800 x 600 Resolution

One available USB 2.0 port (additional ports required for each Auxiliary Readhead in use)